



NOTE.

- Operating pressure 0.4~0.7MPa G  
Valve open: Part (a) Exhaust, Part (b) Supply  
Valve shut: Part (a) Supply, Part (b) Exhaust
- The shape and appearance of assembly differ a little with nominal size and material compared to this drawing.

DIMENSIONS TABLE

UNIT: mm

NOMINAL SIZE	d	DIN PN10				L	D	D1	D2	H	H1	A	A2	A3	P	ACTUATOR TYPE
		C	n	h												
40mm	1 1/2"	45	110	4	18	39	150	71	100	221	75	147	35.0	49	1/4	AR050DA14NN
50	2	56	125	4	18	42	165	81	100	250	83	188	42.5	57	1/4	AR063DA17SN
65	2 1/2	69	145	4	18	46	185	95	100	260	93	188	42.5	57	1/4	AR063DA17SN
80(75)	3	77	160	8	18	46	211	105	100	275	106	188	42.5	57	1/4	AR063DA17SN
100	4	102	180	8	18	56	238	134	100	308	119	281	58.5	59	1/4	AR070DA17SN
125	5	129	210	8	18	66	255	169	140	366	128	355	82.0	82	1/4	AR100DA22XN
150	6	150	240	8	22	71	285	190	140	381	143	355	82.0	82	1/4	AR100DA22XN
200	8	195	295	8	22	87	350	242	140	444	175	432	100.6	101	1/4	AR125DA22XN

13	BOLT	4	SUS304(STAINLESS STEEL)	
12	ACTUATOR	1	PPG etc.	
11	STAND	1	PPG	
10	SCREW	4	SUS304(STAINLESS STEEL)	
9	STEM HOLDER	1	PP	
8	STEM	1	SUS403H(STAINLESS STEEL)	
7	O-RING	4	<input type="checkbox"/> FKM	
6	O-RING	1	<input type="checkbox"/> Others	( )
5	SEAT	1		
4	BUSH	1	BODY/DISC·BUSH	
3	BUSH	1	<input type="checkbox"/> PVC/PP	
2	DISC	1	<input type="checkbox"/> PP/PP	
1	BODY	1	<input type="checkbox"/> PVDF/PVDF	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	BUTTERFLY VALVE TYPE 57 PNEUMATIC MODEL TYPE AR Ass'y DOUBLE ACTING — DIN PN10 40mm (1 1/2") ~ 200mm (8") OPTION: —		
DRAWN	A. Yamamizu	DATE	SCALE
CHECKED	Y. Sato	Nov. 1, 2023	
APPROVED	K. Koushou	DRAWING No. 57-AA107DE	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		