



DIMENSIONS TABLE

Unit: mm

Nominal Size	d	ANSI Class 150				L	D	D ₁	D ₂	H	H ₁	H ₂	I	Actuator Type	Motor Rating Output (Kw)
		C	n	h											
300 ^{mm} 12"	303	432	12	25	129	488	360	235	387	244	301	671	LTRM-01/BRM-1 or LTRH-01/BRM-1 (AUTO-RECOVERY TYPE) (MANUAL RECOVERY TYPE)	0.2	
350	351	476	12	29	129	539	393	235	414	270	328	698			

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

1a	RING	2	STEEL400 (Unichrome Coated)	Used for PP, PVDF Body.
204	GASKET (O)	1	EPDM	
39	BOLT (K)	4	STAINLESS STEEL (SUS304)	
36	STEM BUSH	1	CARBON STEEL (S45C)	
35	ACTUATOR	1	DUCTILE IRON (FCD450) etc.	Epoxy Coat.
7	STEM	1	□ STAINLESS STEEL (SUS403) □ STAINLESS STEEL (SUS316)	
185	O-RING (I)	4	□ EPDM □ FKM □ Others	
6	O-RING (C)	1	()	
3	SEAT	1		
184	SEAT BUSH (B)	1	BODY / DISC SEAT BUSH	
183	SEAT BUSH (A)	1		
2	DISC	1	□ PVC / PP □ PP / PP □ PVDF / PVDF	
1	BODY	1		
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	BUTTERFLY VALVE (TYPE57) ELECTRIC ACTUATED S TYPE ASS'Y □ AUTO-RECOVERY TYPE, □ MANUAL RECOVERY TYPE ANSI Class 150 300 ^{mm} (12") · 350 ^{mm} (14")			
DRAWN	M.Iwakiri	DATE	SCALE	
CHECKED	H.Kawano	SEP.5.2019		
APPROVED	K.Koushou	DRAWING No.		
		57-AE009AE _m		△
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION			